**Journal of Computational Medicine and Informatics**
Vol. 2, No. 1, Jan - Mar 2026, pp. 18-24
ISSN: 3107-3735 (O), DOI: https://doi.org/10.17051/JCMI/02.01.03

# Ontology-Driven Health Informatics System for Intelligent Clinical Knowledge Representation and Reasoning

**G. Balaji**

Professor in Mathematics, Al-Ameen Engineering College (Autonomous), Erode, Tamilnadu, India.
Email: balajivaithesh@gmail.com, 0000-0002-4083-4398

**Article Info**

***Article history:***

Received : 07.11.2025
Revised : 11.12.2025
Accepted : 09.01.2026

***Keywords:***

Ontology,
Health Informatics,
Clinical Decision Support,
Semantic Reasoning,
OWL,
SWRL,
Knowledge Representation

**ABSTRACT**

The increasing amount and diversity of clinical data present serious problems to efficient knowledge representation and smart decision making in contemporary healthcare systems. Traditional data-based methods do not typically provide the means to express semantic relationships and domain knowledge and are more restrictive in their ability to be interpreted and used by clinicians. This paper provides an ontology-based health informatics infrastructure of intelligent clinical knowledge representation and reasoning. The suggested framework makes use of the semantic web technologies with the help of Web Ontology Language (OWL) and Resource Description Framework (RDF) to model a structured clinical knowledge in the form of well-defined entities and relations. The ontology is combined with a rule-based reasoner based on the Semantic Web Rule Language (SWRL) to support automated inference. The system is created with prototeg and the Pellet reasoner to verify and create logic. It is evaluated on MIMIC-III clinical dataset in its subset including the patient symptoms, diagnoses and the treatment records. Experimental evidence has shown that the proposed system has a reasoning accuracy of 91.2 with a better query response time and a better interpretability level than traditional methods of rule-based reasoning. The results of the study reveal the usefulness of ontology-based frameworks in facilitating scalable, transparent and knowledge-based clinical decision support systems.

## 1. INTRODUCTION

The quick shift towards healthcare system digitization has resulted in the explosion of clinical data, such as electronic health records (EHRs), diagnostic reports, medical imaging, and treatment histories. These data sources are however rich in valuable insights to enhance patient care but they are typically heterogeneous, unstructured and spread across various platforms and therefore present a significant challenge in data integration and semantic interoperability [1], [2]. This unstructured representation does not allow any efficient use of clinical information in making intelligent decisions and automated healthcare analytics. The use of conventional machine learning and deep learning methods in healthcare data to predict and diagnose diseases has been extensively utilized. Nevertheless, they are mainly statistical pattern recognition-oriented techniques that do not usually take into account domain-specific knowledge, semantic relations, and logical reasoning abilities [3], [4]. Consequently, they are limited in terms of interpretability which is also an essential request in the clinical setting. Such a framework has been suggested as a promising solution to these challenges, through the use of ontology-based frameworks that facilitate structured and machine-interpretable knowledge representation. SNOomed CT, UMLS and ICD are clinical ontologies, standardized medical concept vocabularies and hierarchies [5], [6]. Additionally, the formal knowledge modeling and interoperability among healthcare systems are supported through semantic web technologies, such as OWL and RDF [7]. Even with these improvements, available ontology-based systems typically do not include built-in reasoning or exhibit quantitative improvement in performance in terms of rigorous evaluation [8], [9].

To overcome such constraints this paper is going to recommend an ontology based health informatics system comprising of both structured knowledge representation and rule based semantic reasoning. The framework presented uses OWL as ontology, SWRL as inference and SPARQL as semantic querying empowering smart clinical knowledge representation and decision support.

Contributions to this Work.

Development of a clinical ontology in OWL to represent structured knowledge.

- Automated generation of SWRL-based inferences.
- Adoption of SPARQL-based semantic query mechanism to retrieve knowledge.
- To test the performance of the system, quantitative assessment with actual clinical data.

## 2. RELATED WORK

### 2.1 Clinical Ontologies

Ontologies in clinical environments have received extensive use in the standardization of medical terminology and facilitating semantic interoperability in healthcare environments. Notable ones are SNOMED CT, which offers a complete clinical terminology describing diseases and their diagnosis, and the Unified Medical Language System (UMLS), which merges several biomedical vocabularies into a single system [1], [2]. Disease coding and epidemiological analysis also extensively involve the use of the International Classification of Diseases (ICD) [3]. Although they provide vocabularies that are structured and hierarchical, these ontologies are more oriented towards knowledge representation and are in general not designed with provision of dynamic reasoning and real-time clinical decision support.

### 2.2 Ontology-Based Clinical Systems

Various ontology-based systems have been suggested in healthcare application such as patient data integration, disease modelling and clinical decision support. The ontology-based frameworks have been employed in modelling patient histories and diagnosis where only the symptoms and associated diseases are linked using predetermined relationships [4], [5]. Graph-based methods also generalize these features by allowing semantic queries and integration of heterogeneous data, via knowledge graphs [6]. Nevertheless, the majority of existing systems focus on knowledge representation and interoperability with limited support to automated reasoning and generation of inferences. Also, a number of studies are not intensively experimentally validated on real-world clinical data, making them less applicable in practice.

### 2.3 Semantic Reasoning in Healthcare

The methods of semantic reasoning, such as description logic, rule-based inference and Semantic Web Rule Language (SWRL) have been used to augment clinical decision-making [7], [8]. These methods allow the implicit knowledge to be derived based on explicitly defined relationships in order to carry out tasks like diagnosis prediction and recommendation of treatment. Though these have its benefits, the current implementations are usually susceptible to scalability issues, reasoning efficiency, as well as integration with large-scale clinical data [9]. Moreover, most of the systems are based on small sets of rules, and the reasoning performance is not measured in terms of standard quantitative measures [10]-[12].

Research Gap

According to the analysis above, the existing approaches have the following limitations:

- Absence of a strong combination between ontology-based knowledge representation and dynamic reasoning processes.
- Scanty quantitative validation with actual clinical data.
- Lack of support of real-time and scalable clinical decision support.
- Poor analysis of reasoning ability as regards accuracy and efficiency.

In a bid to overcome these difficulties, this research presents an ontological-based health informatics framework which incorporates OWL-based knowledge modeling technique coupled with SWRL-based inference methodology and quantitative performance analysis.

## 3. METHODOLOGY

This section outlines the entire methodology of the proposed ontology-based health informatics system. The study is implemented using a systematic pipeline that encompasses the acquisition of clinical data, modeling of semantic knowledge, ontology building, rule based reasoning and inference based decision support. The design of the methodology is such that it is reproducible, scalable and logically consistent in clinical knowledge representation.

### 3.1 System Architecture and Data Processing

The suggested model follows a layered approach whereby clinical information is converted into semantically defined knowledge and then is processed by a reasoning engine to produce smart clinical information. The data that is fed into the system is organized and semi-structured clinical data processed out of the MIMIC-III data which includes the patient demographics, symptom history, diagnosis code and treatment history. The Fig. 1 shows the general system architecture and data processing flow of the offered ontology-based health informatics system.

define the clinical dataset as:

$$D = \{d_1, d_2, d_3, \dots, d_n\} \quad (1)$$

where each $d_i$represents an individual patient record. Each record is further decomposed into feature sets:

$$d_i = \{P_i, S_i, Di_i, T_i\} \quad (2)$$

where $P_i$ denotes patient attributes, $S_i$ represents symptoms, $Di_i$ denotes diagnoses, and $T_i$ represents treatments.

The preprocessing phase includes the normalization, treatment of missing values and mapping raw clinical properties to standard ontology concepts. Such transformation guarantees heterogeneous data is transformed into a common semantic representation that can be integrated in ontology.





**Fig. 1.** System Architecture and Data Processing Workflow for Ontology-Driven Clinical Knowledge Representation

### 3.2 Ontology Construction and Knowledge Representation

The ontology is created with the help of Methontology framework that provides systematic definition of domain knowledge with a conceptualization and formalization process. The ontology is expressed in terms of a directed labeled graph:

$$O = (C, R, I) \quad (3)$$

where $C$ denotes the set of classes, $R$ represents relationships (object properties), and $I$ represents instances.

The core class set is defined as:

$$C = \{Patient, Disease, Symptom, Treatment, Diagnosis\} \quad (4)$$

Relationships between these classes are defined as:

$$R = \{\text{asSymptom}, diagnosedWit\text{h}, treatedBy\} \quad (5)$$

Each relationship is represented as an RDF triplet:

$$(s, p, o) \quad (6)$$

where $s$ is the subject, $p$ is the predicate, and $o$ is the object. For example:

$$(Patient_{001}, \text{asSymptom}, Fever) \quad (7)$$

It is coded in Web ontology language (OWL) allowing formal semantics and machine interpretability. OWL provides logical consistency, as well as reasoning based on description logic.

### 3.3 Semantic Reasoning Model

The reasoning model would be used to derive implicit clinical knowledge based on explicitly defined ontology relationships. This is done by incorporating Semantic Web Rule Language (SWRL) rules.

Define the set of symptoms related to a patient pbe to be:

$$S(p) = \{s_1, s_2, \dots, s_k\} \quad (8)$$

A general inference function can be expressed as:

$$f: S(p) \rightarrow D(p) \quad (9)$$

where $D(p)$ represents the inferred disease set.

A typical SWRL rule is expressed in first-order logic form as:

$$\forall p\ (\text{asSymptom}(p, Fever) \wedge \text{asSymptom}(p, Coug\text{h}) \rightarrow diagnosedWit\text{h}(p, Influenza)) \quad (10)$$

This rule allows the system to deduce disease states by looking at combinations of symptoms. Such rules are many and are designed to depict complicated clinical relationships.

The reasoning process is implemented in the Pellet reasoner, which does consistency checking, classification, and inference generation. The reasoner assesses all logical claims, and uses SWRL rules until there are no more inferences to be made.

### 3.4 Algorithmic Workflow

The general rationale methodology is applied in form of an iterative algorithm that incorporates data processing, ontology mapping and inference generation.

**Algorithm 1: Ontology-Driven Clinical Reasoning**

The algorithm starts with loading the clinical data and initiating the ontology model. The patient records are matched to the ontology classes and properties, producing RDF triplets. The ontology is then processed by the SWRL rule set, and invoked to run logical inference by the Pellet reasoner. The derived associations are stored and are availed in a SPARQL query interface as a part of decision support.

The process of reasoning could be formally represented as follows:

$$O' = O \cup f(S(p)) \quad (11)$$

where $O'$ represents the enriched ontology after inference.

When no further inferred knowledge is based on the ontology, the algorithm stops.

### 3.5 Tools and Implementation Environment

Protégé is an ontology development system that is used to implement the system so that OWL-based models can be easily created and visualised. It is integrated with the Pellet reasoner, used to do semantic reasoning and logical validation. The query language is SPARQL, which is used to get both explicit and inferred knowledge in the ontology. This whole structure is implemented in a controlled computational environment to guarantee uniform assessment. These tools together offer a powerful platform on semantic knowledge modeling and reasoning in healthcare applications.

### 3.6 Multi-Rule Semantic Reasoning Framework

In order to improve the inferential power of the suggested system, a multi-rule system of reasoning is presented. The system also uses multiple SWRL rules as opposed to single condition inference because it embraces composite and hierarchical reasoning.

Let the symptom set for a patient $p$be:

$$S(p) = \{s_1, s_2, \dots, s_k\} \quad (12)$$

The disease inference is modeled as:

$$D(p) = \bigcup_{i=1}^{m} f_i\,(S(p)) \quad (13)$$

where each $f_i$represents an independent rule mapping symptoms to diseases.

**Composite Rule Set**

The reasoning system includes multiple interacting rules:

**Rule 1 (Respiratory Disease Inference):**

$$\text{asSymptom}(p, Fever) \wedge \text{asSymptom}(p, Coug\square) \rightarrow diagnosedWit\square(p, Influenza)$$

**Rule 2 (Severity Escalation Rule):**

$$diagnosedWit\square(p, Influenza) \wedge \square asSymptom(p, S\square ortnessOfBreat\square) \rightarrow diagnosedWit\square(p, SevereRespiratoryInfection)$$

**Rule 3 (Treatment Recommendation Rule):**

$$diagnosedWit\square(p, Influenza) \rightarrow treatedBy(p, AntiviralDrugs)$$

**Rule 4 (Chronic Condition Interaction):**

$$diagnosedWit\square(p, Diabetes) \wedge diagnosedWit\square(p, Influenza) \rightarrow Hig\square RiskPatient(p)$$

This layered reasoning allows the system to derive:

- Primary diagnosis
- Secondary complications
- Treatment recommendations
- Risk stratification

The inference process becomes hierarchical, where outputs of earlier rules serve as inputs for subsequent rules.

### 3.7 Time Complexity Analysis

The computational complexity of the proposed ontology-based reasoning system depends on three major components: ontology size, number of rules, and reasoning operations.

Let:

- $|\ C\ |$= number of ontology classes
- $|\ R\ |$= number of relationships
- $|\ I\ |$= number of instances
- $|\ Rules\ |$= number of SWRL rules

**Ontology Construction Complexity**

Ontology creation involves mapping each data instance to ontology classes:

$$T_{ontology} = O(|\ I\ | \cdot |\ C\ |) \quad (14)$$

**Reasoning Complexity**

The reasoning process evaluates all rules over all instances:

$$T_{reasoning} = O(|\ Rules\ | \cdot |\ I\ | \cdot k) \quad (15)$$

where $k$is the average number of conditions per rule.

For multi-rule hierarchical reasoning:

$$T_{total} = O(|\ Rules\ | \cdot |\ I\ | \cdot k + |\ R\ |) \quad (16)$$

**SPARQL Query Complexity**

Query execution over RDF triples:

$$T_{query} = O(|\ Triples\ |) \quad (17)$$

where:

$$|\ Triples\ | = |\ I\ | \cdot |\ R\ | \quad (18)$$

**Overall Complexity**

$$T_{overall} = O(|\ I\ | \cdot |\ C\ | + |\ Rules\ | \cdot |\ I\ | \cdot k) \quad (19)$$

It means that the system will scale in direct proportion to the size of patient records and can be quite complex in response to rule complexity. Computational overhead is alleviated by using optimized reasoning engines like Pellet.

### 3.8 Workflow of the Proposed System

The overall workflow of the system follows a sequential and iterative pipeline that transforms raw clinical data into actionable knowledge.

**Step 1: Data Acquisition**

Clinical data is extracted from the MIMIC-III dataset and structured into patient-level records.

**Step 2: Data Preprocessing**

Data normalization, missing value handling, and semantic mapping to ontology classes are performed.

**Step 3: Ontology Mapping**

Each data element is converted into RDF triplets and integrated into the OWL ontology.

**Step 4: Rule Injection**

SWRL rules are defined and applied to the ontology to establish logical relationships.

**Step 5: Reasoning Execution**

The Pellet reasoner processes the ontology and rules to infer implicit knowledge.

**Step 6: Knowledge Enrichment**

New relationships such as inferred diagnoses and risk categories are added to the ontology.

**Step 7: Query and Decision Support**

SPARQL queries retrieve both explicit and inferred knowledge for clinical decision-making.

**Formal Workflow Representation**

$$D \rightarrow Preprocessing \rightarrow O \rightarrow Rules \rightarrow Reasoner \rightarrow O' \rightarrow Query \rightarrow Output \quad (20)$$

where:

- $O$= initial ontology
- $O'$= enriched ontology after reasoning

## 4. Dataset and Implementation

### 4.1 Dataset

The proposed health informatics system based on ontology is evaluated experimentally, and it is implemented using a subset of the MIMIC-III (Medical Information Mart on Intensive Care) clinical database. MIMIC-III is a publicly available and large-scale dataset, which consists of the de-identified health-related data of patients with intensive care unit admissions. It contains various clinical data like patient demographics, physiological measurements, diagnostic records and treatment procedures. In this case, a subgroup of 5,000 patient records is chosen to guarantee the possibility of computations and at the same time provide enough diversity to conduct some evaluation. A patient record consists of standardized clinical data (e.g., age and gender), symptoms data (e.g., fever, cough and respiratory conditions), diagnosis codes (e.g., based on ICD, disease classifications), and treatment data (e.g., medications and clinical interventions). Preprocessing of the dataset is done to eliminate inconsistencies and missing values, and then normalization is done to standardize features. Then, it transforms clinical features to ontology terms, which allows representing and integrating them into the knowledge model on a semantic level.

### 4.2 Implementation Environment

The proposed semantic web based ontology-driven health informatics system is worked out in a controlled computational environment involving use of semantic web technologies and ontology engineering tools to ensure reproducibility and consistency of performance. The ontology model is created with the help of Protégé 5.5 which is an open-source ontology editor that allows the representation and visualization of knowledge in OWL. The Web ontology language (OWL 2) and resource description framework (RDF) are used to encode clinical entities and their associations to provide interoperability and allow formal semantic modeling. The reasoning is implemented by the Pellet reasoner (2.3.1) which is a logical consistency checker, class hierarchy classifier and a rule-based inferential system on SWRL rules. Semantic queries are implemented with SPARQL 1.1 and thus explicit and inferred knowledge can be efficiently retrieved. System is implemented on a work station which has the following hardware specifications: Intel Core i7 processor (3.4 GHz), RAM of 16GB and SSD storage of 512GB. Ontology reasoning is mostly a CPU-intensive process; hence, no GPUs are being accelerated in this implementation. The software environment entails Java Development Kit (JDK 1.8) and is run in a windows 10 64-bit operating system. The dataset is split to create two subsets (training and testing) based on an 80:20. The ontology and SWRL rules are defined by training subset and populated by it, and reasoning performance and accuracy of the inference is tested with the help of the testing subset. They are performed several times in order to be stable and consistent.

## 5. Performance Evaluation

### 5.1 Evaluation Metrics

Standard classification metrics and system level metrics are used to give a quantitative evaluation of the performance of the proposed ontology-driven reasoning system.

Accuracy measures the proportion of correctly inferred diagnoses:

$$Accuracy = \frac{TP + TN}{TP + TN + FP + FN} \quad (21)$$

Precision evaluates the correctness of positive predictions:

$$Precision = \frac{TP}{TP + FP} \quad (22)$$

Recall measures the system's ability to identify relevant clinical conditions:

$$Recall = \frac{TP}{TP + FN} \quad (23)$$

The F1-score provides a harmonic balance between precision and recall:

$$F1 = 2 \cdot \frac{Precision \cdot Recall}{Precision + Recall} \quad (24)$$

Alongside the measures of classification, reasoning time will be measured as a measure of the computational efficiency, which is the mean time taken by the Pellet reasoner to reason over ontology rules and make inferences.

### 5.2 Experimental Results

The test subset of the MIMIC-III data is used to evaluate the performance of the proposed system. Table 1 summarizes the results.

**Table 1.** Performance Metrics of the Proposed System

| Metric | Value |
|---|---|
| Accuracy | 91.2% |
| Precision | 89.5% |
| Recall | 88.7% |
| F1-score | 89.1% |
| Avg. Reasoning Time | 120 ms |

The findings show that the suggested system has a high diagnostic accuracy and has an efficient performance of reasoning. The fairly even accuracy and recall scores indicate that the system is highly effective as reduces the risk of false positives and false negatives, which is essential in clinical decision situations.





**Fig. 2.** Performance Comparison of Proposed and Existing Methods

### 5.3 Comparative Analysis

To confirm that the proposed approach is effective, it is compared to the traditional rule-based systems and machine learning-based models. Table 2 shows the comparison.

**Table 2.** Comparative Analysis

| Method | Accuracy | Reasoning Capability |
|---|---|---|
| Rule-Based System | 82% | Limited |
| ML Model | 88% | No semantic reasoning |
| Proposed System | 91.2% | Advanced |

The proposed system is more than 9.2 percent more accurate than conventional rule-based systems, and this is mostly because it can be used to model complex semantic relationships. Improvement of 3.2 percent compares with machine learning models to show the benefit of a combination of domain knowledge and reasoning mechanisms. The proposed ontology-driven framework, in contrast to machine learning techniques which are not transparent and explainable, offers transparent and explainable reasoning allowing clinicians to follow the reasoning process. This is a significant anticipated need in medical applications.





**Fig. 3.** Reasoning Time vs Dataset Size

## 6. DISCUSSION

The experimental findings validate that ontology-based knowledge representation and rule-based reasoning can indeed help improve the performance of clinical decision support systems to a large extent. The high accuracy and equal precision-recall results show that the system is able to predict disease conditions with a lot of accuracy basing on symptom patterns. The fact that the proposed approach can be used to offer interpretable and explainable results is one of its strongest advantages as it overcomes a significant drawback of standard machine learning models. The system can be used to make the clinical choices based on the domain knowledge and not on the statistical correlation alone through the use of semantic relationships and logical rules.

Moreover, a fairly short reasoning time (120 ms) indicates that the system has low-computational efficiency and can be used in near real-time clinical scenarios. This renders the framework feasible to be implemented in a decision support setting where response is of paramount importance. Nevertheless, there are limitations of the system as well. The quality and completeness of the ontology is very critical towards its performance. The absence or distortion of connections can result in draw conclusions or wrong inferences. Also, the reasoning process can be computationally expensive as the ontology and rule set can grow in size, which is challenging to scale. The use of predefined rules is also a limiting factor because it might not be able to encompass all potential clinical situations. The knowledge base needs to be updated continuously and validated by experts to ensure the accuracy and relevance of the knowledge base.

## CONCLUSION AND FUTURE WORK

This paper is an overview of an ontology-based health informatics system to support intelligent clinical knowledge representation and intelligent reasoning. The suggested system combines rule-based inference with the semantic web technologies to deal with the obstacles of heterogeneous and unstructured clinical data. The system facilitates structured, interpretable, and machine-understandable knowledge representation in clinical knowledge by the use of OWL to represent the knowledge and SWRL to reason about it. The experimental analysis performed on the MIMIC-III dataset proves that the offered system has high performance, and its accuracy is 91.2, accompanied by a balance between the precision and recall. Moreover, the system demonstrates good reasoning rates with an average of 120 ms to reason suggesting its applicability in near real-time clinical decision support functions. The comparative analysis also validates the superiority of the suggested strategy over the traditional rule-based systems and machine learning models regarding the accuracy and interpretability. One of the important contributions of this work can be considered to be the combination of ontology-based modeling with multi-rule semantic reasoning, which allows making decisions in a transparent and explainable way. In contrast to black-box models, the proposed system offers traceable inference paths, which are required to make clinical trust and validation. Moreover, the provision of scalability and extensibility to future healthcare applications is guaranteed by the modular architecture and semantic representation. Although there are these benefits, some limitations still exist. The performance of the system can be determined by the completeness and quality of ontology, and scalability can become an issue when dealing with large knowledge bases and complex rules. Also, it might be a problem with the flexibility to unknown clinical situations because of the use of predetermined rules. Subsequent research will be conducted to improve the framework by combining deep learning models and ontology-based reasoning in order to create hybrid intelligent systems. Additional advancements involve real-time usage in clinical settings, using multi-disease and multi-modes of data, and optimization of reasoning scale in large-scale healthcare systems.

## REFERENCES

1. M. Ashburner *et al.*, “Gene ontology: tool for the unification of biology,” *Nature Genetics*, vol. 25, no. 1, pp. 25–29, 2000.
2. T. Berners-Lee, “The Semantic Web,” in *Proc. XML 2000*, World Wide Web Consortium (W3C), 2000.
3. W. Ceusters, B. Smith, and L. Goldberg, “A terminological and ontological analysis of the NCI Thesaurus,” *Methods of Information in Medicine*, vol. 44, no. 4, pp. 498–507, 2005.
4. D. L. Cook, J. L. Mejino, and C. Rosse, “The foundational model of anatomy: A template for the symbolic representation of multi-scale physiological functions,” in *Proc. IEEE Eng. Med. Biol. Soc.*, 2004, pp. 5415–5418.
5. Z. Pincus and M. A. Musen, “Contextualizing heterogeneous data for integration and inference,” in *Proc. AMIA Symp.*, Washington, DC, USA, 2003.
6. A. L. Rector, J. E. Rogers, P. E. Zanstra, and E. Van Der Haring, “OpenGALEN: Open source medical terminology and tools,” in *Proc. AMIA Annu. Symp.*, 2003, p. 982.
7. J. Seidenberg and A. Rector, “Web ontology segmentation: Analysis, classification and use,” in *Proc. Int. World Wide Web Conf. (WWW)*, Edinburgh, Scotland, 2006.
8. V. Sugumaran and V. C. Storey, “Ontologies for conceptual modeling: Their creation, use, and management,” *Data & Knowledge Engineering*, vol. 42, no. 3, pp. 251–271, 2002.
9. W3C, “Resource Description Framework (RDF) model and syntax specification,” 1999.
10. W3C, “OWL Web Ontology Language: Semantics and abstract syntax,” 2003.
11. W3C, “Simple Knowledge Organization System (SKOS),” 2005.
12. R. Vdovjak and G.-J. Houben, “RDF-based architecture for semantic integration of heterogeneous information sources,” in *Proc. Workshop on Information Integration on the Web*, Eindhoven University of Technology, 2001.