Article

A REVIEW ON DEEP LEARNING-BASED SEGMENTATION ALGORITHMS FOR MEDICAL IMAGES

M.Kavitha

Department of ECE,
Saveetha School of Engineering,
Saveetha Institute of Medical and Technical Sciences,
Saveetha University,
Chennai,
India

E-mail: kavithavlsime@gmail.com

Abstract: Medical image segmentation is a crucial task in healthcare, enabling accurate diagnosis, treatment planning, and disease monitoring. Traditional segmentation techniques, such as thresholding, region-growing, and deformable models, often struggle with handling complex anatomical structures and noise. Deep learning-based approaches, particularly convolutional neural networks (CNNs), recurrent neural networks (RNNs), and hybrid models, have emerged as powerful alternatives, offering improved accuracy and automation. This paper provides a comprehensive review of deep learning-based segmentation algorithms, discussing their methodologies, advantages, and limitations. Additionally, we explore the applications of these models across various medical imaging modalities, such as MRI, CT, and ultrasound. The challenges of deep learning models, including data dependency, computational requirements, and generalization, are also addressed. Finally, we highlight future research directions, emphasizing the need for self-supervised learning, federated learning, and explainability in deep learning-driven medical image segmentation.

Keywords: Deep Learning, Medical Image Segmentation, Convolutional Neural Networks, U-Net, Hybrid Models, AI in Healthcare.

Journal of Computational Medicine and Informatics
Volume 1 Issue 1 (Jan-Mar)
Submitted Date 12 Jan 2025
Received Date 13 Feb 2025
Accepted Date 23 Mar 2025
Online at https: www.jmcijournal.com

1. Introduction

Medical image segmentation is a fundamental task in medical imaging analysis, aiming to identify and delineate anatomical structures such as organs, tissues, and tumors. Accurate segmentation is essential for numerous clinical applications, including disease diagnosis, treatment planning, and surgical navigation. Traditional segmentation techniques, such as thresholding, region-growing, and deformable models, often require extensive preprocessing and manual intervention. These methods are prone to variability, as they rely on predefined heuristics and are sensitive to noise, intensity inhomogeneity, and anatomical variations.With the advancements in artificial intelligence, deep learning has emerged as a transformative approach in medical image analysis. Deep learning-based models leverage large datasets to automatically learn hierarchical features, improving segmentation accuracy and reducing reliance on manual preprocessing. Convolutional neural networks (CNNs), recurrent neural networks (RNNs), and hybrid architectures have demonstrated superior performance in segmenting complex medical images with minimal human intervention. By integrating deep learning into medical image segmentation, researchers and clinicians can achieve more precise and reproducible results, ultimately enhancing patient care.

This paper provides a comprehensive review of deep learning-based segmentation algorithms, categorizing them into CNN-based, RNN-based, and hybrid models. We discuss their methodologies, advantages, and challenges, along with their applications across various imaging modalities such as MRI, CT, and ultrasound. Furthermore, we highlight the limitations of current deep learning models, including data dependency, computational requirements, and interpretability concerns. Finally, we explore future research directions, emphasizing the importance of self-supervised learning, federated learning, and explainability in deep learning-driven medical image segmentation.

2. Literature Review

Traditional medical image segmentation techniques have been extensively studied in prior research, forming the foundation for many early advancements in the field. Ma, Tavares, and Jorge (2009) classified segmentation algorithms into three primary categories: **threshold-based methods, pattern recognition-based techniques, and deformable models**. Each of these approaches has been applied to medical imaging with varying degrees of success, depending on the complexity of the anatomical structures, the quality of the imaging modality, and the specific clinical application.

Threshold-Based Segmentation

Threshold-based methods are among the simplest and most widely used segmentation techniques, relying on pixel intensity differences to distinguish objects from the background. These methods work by defining a threshold value, above or below which pixels are classified into different regions. A common example is **Otsu's thresholding**, which automatically determines an optimal threshold by minimizing intra-class variance. Although thresholding is computationally efficient and easy to implement, it struggles in cases where image intensity varies due to artifacts, noise, or different imaging conditions. For example, in MRI and CT scans, structures with overlapping intensity distributions may be difficult to segment accurately, leading to errors such as over-segmentation (including unwanted regions) or under-segmentation (missing crucial anatomical features). Additionally, thresholding lacks spatial awareness, meaning it does not consider the contextual relationships between neighboring pixels, limiting its effectiveness in segmenting complex structures such as tumors, blood vessels, or organs with indistinct boundaries.

Pattern Recognition-Based Segmentation

To address the limitations of thresholding, pattern recognition techniques have been developed, incorporating **statistical learning models** to improve segmentation accuracy. These techniques rely on classifying pixels or regions based on their statistical properties, often requiring labeled training datasets for supervised learning approaches. Supervised classification methods such as **support vector machines (SVMs), decision trees, and artificial neural networks (ANNs)** have shown promise in distinguishing between different tissue types. However, these approaches require large, well-annotated datasets, which can be labor-intensive to produce and subject to inter-observer variability. The dependency on manually labeled training data also limits their applicability to new datasets where variations in imaging protocols or patient characteristics may lead to model performance degradation.


In contrast, **unsupervised classification techniques**—such as **fuzzy c-means clustering, k-means clustering, and Gaussian mixture models (GMMs)**—do not require labeled data. These methods automatically group pixels based on their statistical similarity, making them useful for segmenting images where prior annotations are unavailable. However, unsupervised learning approaches often struggle with generalization, as they do not inherently capture the spatial relationships within an image. For instance, clustering-based methods might misclassify similar-looking but anatomically distinct regions, leading to segmentation errors in complex medical images. Additionally, these methods can be sensitive to initialization parameters, requiring careful tuning to achieve optimal performance.

Deformable Models for Medical Image Segmentation

Another widely used approach in traditional medical image segmentation is the use of **deformable models**, which account for shape priors and geometric constraints to improve segmentation accuracy. **Active contour models (snakes)** and **level-set methods** are popular techniques that iteratively refine segmentation boundaries based on energy minimization principles. These methods are particularly effective for segmenting structures with smooth and well-defined contours, such as the boundaries of organs or tumors. However, they require careful parameter selection and may struggle in cases where object boundaries are highly irregular or obscured by noise and artifacts.

Overall, while traditional segmentation methods such as thresholding, pattern recognition, and deformable models have been instrumental in advancing medical image analysis, they exhibit several limitations, particularly in handling images with complex anatomical structures, low contrast, or high variability. These challenges have led researchers to explore more advanced machine learning and deep learning-based approaches, which leverage data-driven techniques to achieve higher segmentation accuracy and robustness across different imaging modalities.

Fig.1: Traditional and Deep learning-based segmentation



Deformable models, such as active contours (snakes) and level sets, have been widely applied to medical image segmentation due to their ability to handle shape variations. These models evolve over time to fit object boundaries by minimizing an energy function that balances internal smoothness constraints with external image forces. While effective for segmenting complex anatomical structures, deformable models require careful parameter tuning and suffer from high computational costs, making them less suitable for real-time applications.With the rapid advancements in deep learning, researchers have shifted towards automated learning-based segmentation approaches that overcome the limitations of traditional methods. Convolutional neural networks (CNNs), introduced in medical imaging by Ronneberger et al. (2015) through the U-Net architecture, have significantly improved segmentation accuracy by leveraging hierarchical feature extraction. U-Net employs an encoder-decoder structure with skip connections, enabling precise boundary delineation even with limited training data. Subsequent models, such as V-Net (Milletari et al., 2016), extend U-Net to 3D medical imaging, making it suitable for volumetric segmentation tasks.

Further advancements in deep learning-based segmentation have introduced models such as DeepLab (Chen et al., 2017), which incorporates atrous spatial pyramid pooling to capture multi-scale contextual information. This approach enhances segmentation accuracy, particularly in medical images with fine structural details. More recently, transformer-based architectures, such as Swin-UNet (Cao et al., 2021), have emerged as a powerful alternative to traditional CNNs. These models utilize self-attention mechanisms to capture long-range dependencies within medical images, improving segmentation robustness and generalization.

Despite the superior performance of deep learning models, several challenges remain. High computational requirements, the need for large annotated datasets, and difficulties in model interpretability hinder their widespread clinical adoption. Many deep learning models function as black boxes, making it difficult for clinicians to understand their decision-making processes. Additionally, models trained on specific datasets may fail to generalize to new imaging modalities or patient populations, necessitating domain adaptation techniques.Overall, while traditional segmentation techniques remain relevant for specific applications, deep learning-based approaches have demonstrated remarkable improvements in segmentation accuracy, automation, and scalability. Future research should focus on addressing the limitations of deep learning models by integrating self-supervised learning, federated learning, and explainable AI to enhance their clinical applicability.

3. Deep Learning-Based Segmentation Techniques

Deep learning-based segmentation techniques have revolutionized medical image analysis by enabling automated and highly accurate delineation of anatomical structures and pathological regions. These techniques primarily rely on Convolutional Neural Networks (CNNs), which extract spatial features from medical images to generate precise segmentation masks. Popular architectures such as U-Net, V-Net, and DeepLab utilize encoder-decoder structures, skip connections, and atrous convolutions to enhance segmentation accuracy. Recent advancements have introduced hybrid models, such as Swin-UNet and Vision Transformers (ViTs), which incorporate attention mechanisms to capture global dependencies and improve feature representation. Additionally, self-supervised and semi-supervised learning approaches have been developed to reduce reliance on large labeled datasets, while federated learning ensures privacy-preserving model training across multiple institutions. To further enhance efficiency, lightweight architectures are being designed for real-time clinical applications. As these deep learning techniques continue to evolve, they hold immense potential in improving diagnostic precision, treatment planning, and patient outcomes across various medical imaging modalities.





Fig.2: Deep Learning-Based Segmentation Techniques

3.1 Convolutional Neural Networks (CNNs)

Convolutional Neural Networks (CNNs) are the foundation of modern deep learning-based image segmentation, particularly in medical imaging. Among the most effective architectures, U-Net, V-Net, and DeepLab have demonstrated significant success in segmenting complex medical images. U-Net utilizes an encoder-decoder structure with skip connections, allowing for precise boundary delineation while retaining spatial details. V-Net extends U-Net's capabilities to three-dimensional (3D) segmentation, making it particularly suitable for volumetric medical images such as MRI and CT scans. DeepLab enhances segmentation accuracy by incorporating atrous (dilated) convolution, which expands the receptive field without reducing resolution, and fully connected Conditional Random Fields (CRFs) to refine segmentation outputs. These models are trained using annotated medical image datasets and optimized with loss functions like cross-entropy or Dice coefficient loss. To improve generalization, data augmentation techniques such as rotation, scaling, and contrast adjustments are applied. Performance is evaluated using metrics like Dice Similarity Coefficient (DSC), Intersection over Union (IoU), and pixel-wise accuracy, ensuring that the models achieve robust and clinically relevant segmentation results.

Fig.3: Convolutional Neural Networks Diagram



3.2 Recurrent Neural Networks (RNNs)

Recurrent Neural Networks (RNNs), including Long Short-Term Memory (LSTM) and Gated Recurrent Units (GRU), are widely used for temporal analysis in medical imaging. Unlike traditional Convolutional Neural Networks (CNNs), which primarily focus on spatial features, RNNs specialize in capturing temporal dependencies in sequential data. This makes them particularly useful for segmenting time-series medical images, such as cardiac MRI and ultrasound scans, where anatomical structures change over time. LSTM networks use memory cells to retain long-term dependencies, mitigating the vanishing gradient problem that affects standard RNNs. Similarly, GRUs simplify LSTM functionality by using gating mechanisms to regulate information flow, reducing computational complexity while maintaining strong performance in temporal modeling.

To implement RNN-based segmentation, sequential medical images are first preprocessed and normalized to ensure consistency across frames. The data is then passed through an RNN-based architecture, often combined with CNNs to extract spatial and temporal features simultaneously. Loss functions such as Dice loss or cross-entropy loss are employed to optimize segmentation accuracy. Additionally, techniques like data augmentation and temporal smoothing are applied to enhance model generalization. Performance is evaluated using metrics such as Temporal Dice Similarity Coefficient (tDSC) and Frame-wise Intersection over Union (IoU) to measure segmentation stability across frames. These methods ensure that RNN-based models provide accurate and temporally consistent segmentation for dynamic medical imaging applications.

3.3 Hybrid and Transformer-Based Models

Recent advancements in deep learning have led to the development of hybrid models that integrate Convolutional Neural Networks (CNNs) with attention mechanisms, particularly the Transformer architecture. Traditional CNNs excel at capturing local spatial features, but they struggle with long-range dependencies. To address this limitation, attention-based models such as Vision Transformers (ViTs) and Swin-UNet have been introduced. These models utilize self-attention mechanisms to dynamically focus on important regions in an image, improving both feature representation and spatial understanding. Unlike standard CNNs, Transformers process images as sequences of patches, enabling them to model global relationships more effectively, which is particularly beneficial for complex medical image segmentation tasks.

Swin-UNet, a hierarchical vision Transformer model, extends the U-Net architecture by incorporating a shifted window attention mechanism. This design efficiently balances local and global feature extraction, allowing for precise segmentation of medical images such as CT and MRI scans. The model operates by dividing images into non-overlapping patches and applying self-attention within small windows, progressively capturing long-range dependencies through hierarchical feature aggregation. Similarly, ViTs employ multi-head self-attention (MHSA) to process entire images holistically, ensuring that even subtle patterns and structural variations are effectively recognized. These mechanisms significantly enhance segmentation accuracy by refining boundary delineation and improving contextual awareness.To implement these hybrid models, medical images are preprocessed by resizing, normalizing, and dividing them into smaller patches. The images are then fed into the Transformer-based network, where attention layers refine feature extraction and segmentation outputs. Loss functions such as Dice loss or focal loss are used to optimize model performance, while advanced training techniques like data augmentation and transfer learning further improve generalization. Evaluation metrics, including Dice Similarity Coefficient (DSC), Intersection over Union (IoU), and Hausdorff Distance, are employed to assess segmentation accuracy. By integrating CNNs with attention mechanisms, these hybrid models offer a robust solution for precise and efficient medical image segmentation, outperforming traditional architectures in complex clinical applications.

4. Challenges in Deep Learning-Based Segmentation

One of the primary challenges in developing deep learning models for medical image segmentation is data dependency. Training robust models requires large, high-quality, and well-annotated datasets, which can be difficult to obtain due to ethical concerns, patient privacy regulations, and institutional data-sharing restrictions. Unlike natural image datasets, where large-scale labeled images are readily available, medical imaging data often require expert radiologists or clinicians for annotation, making the labeling process time-consuming and costly. Additionally, variations in imaging protocols, equipment, and patient demographics can introduce bias into datasets, further complicating model training and validation. Techniques such as federated learning and synthetic data generation using generative adversarial networks (GANs) are being explored to mitigate data scarcity and privacy concerns while maintaining model performance.

Table.1: Tabulation for Traditional and Deep learning-based segmentation

Aspect	Existing Paper (Traditional Segmentation)	Proposed Paper (Deep Learning-Based Segmentation)
Segmentation Approaches	Threshold-based, pattern recognition, deformable models	CNNs, FCNs, U-Net, attention mechanisms, transformers
Strengths	Works well for specific structures with clear boundaries, computationally efficient	Handles complex anatomical structures, learns from data, higher accuracy
Limitations	Sensitive to noise, requires manual tuning, struggles with variations	Requires large datasets, high computational cost, less interpretability
Flexibility	Less flexible, often rule-based	More adaptable, generalizes across imaging modalities
Applications	CT, MRI, ultrasound segmentation using classic techniques	CT, MRI, ultrasound segmentation using deep learning
Challenges	Noise sensitivity, lack of generalization, difficulty handling complex topologies	Data scarcity, model interpretability, high computational complexity
Future Trends	Hybrid approaches, improved mathematical models	Self-supervised learning, transformer-based models, interpretable AI

Another significant limitation is the computational complexity of deep learning models. State-of-the-art architectures, such as U-Net, Vision Transformers (ViTs), and Swin-UNet, require extensive computational resources, including high-end GPUs or specialized hardware like TPUs (Tensor Processing Units) for efficient training and inference. The large number of parameters in these models leads to high memory consumption and long training times, making deployment in real-time clinical settings challenging. To address this, model optimization techniques such as knowledge distillation, pruning, and quantization are being utilized to reduce computational demands without significantly compromising accuracy. Additionally, cloud-based solutions and distributed computing frameworks enable training on large datasets, but they introduce concerns related to data security and latency in medical applications.




Fig.4: Comparison of Traditional and Deep learning-based segmentation

Beyond computational demands, generalization and interpretability remain critical challenges. Deep learning models trained on specific datasets often struggle to generalize across different imaging modalities, institutions, and patient populations. Domain shifts due to variations in scanner types, acquisition protocols, and disease presentations can lead to degraded performance in real-world clinical settings. Transfer learning, domain adaptation, and contrastive learning are being explored to enhance model robustness across diverse datasets. Furthermore, deep learning models often function as "black boxes," making it difficult to interpret their decision-making process. The lack of transparency raises concerns in clinical adoption, where explainability is essential for trust and validation. To improve interpretability, techniques such as attention maps, class activation mapping (CAM), and explainable AI (XAI) frameworks are being integrated into deep learning pipelines to provide insights into model predictions, enhancing their clinical applicability and acceptance.

5. Applications in Medical Imaging Deep learning-based segmentation

Applications in Medical Imaging Deep learning-based segmentation algorithms have revolutionized medical image analysis, enabling precise and automated identification of anatomical structures and pathological abnormalities across various imaging modalities. These models, particularly Convolutional Neural Networks (CNNs), Transformers, and hybrid architectures, have demonstrated exceptional performance in segmenting organs, tissues, and lesions, aiding in early diagnosis, treatment planning, and disease monitoring. Below, we explore their applications in different medical imaging techniques.

5.1 Magnetic Resonance Imaging (MRI)

MRI is widely used for soft tissue visualization, making it essential for neurological and cardiac applications. Deep learning models, such as U-Net and its variants, have been extensively employed for brain tumor segmentation, helping to delineate tumor boundaries in gliomas, meningiomas, and metastatic lesions. Advanced architectures like Vision Transformers (ViTs) enhance segmentation accuracy by capturing global contextual information. In cardiac MRI, segmentation models assist in left and right ventricle delineation, myocardial segmentation, and scar tissue detection, which are crucial

for assessing heart diseases such as cardiomyopathies and myocardial infarctions. Additionally, MRI-based segmentation is used in musculoskeletal imaging for cartilage and ligament analysis.

5.2 Computed Tomography (CT)

CT imaging provides high-resolution anatomical details and is commonly used for lung, liver, and abdominal imaging. Deep learning-based segmentation models play a pivotal role in lung nodule detection, which is critical for early lung cancer diagnosis. Automated segmentation algorithms aid in distinguishing malignant and benign nodules, improving diagnostic accuracy. In liver segmentation, CNN-based approaches help delineate liver tumors and assist in surgical planning for hepatocellular carcinoma (HCC) and liver metastases. Moreover, deep learning is employed in abdominal organ segmentation, including kidney, pancreas, and spleen segmentation, to support disease diagnosis and treatment monitoring.

5.3 Ultrasound Imaging

Ultrasound is a widely used imaging modality due to its real-time capability and non-invasive nature, making it essential for fetal and cardiovascular imaging. Deep learning algorithms assist in fetal organ segmentation, including brain, heart, and kidney structures, enabling early detection of congenital anomalies. In echocardiography, automated segmentation of heart chambers, myocardium, and valves helps in diagnosing cardiovascular diseases, such as heart failure and valve disorders. Ultrasound-based segmentation is also applied in breast cancer screening, where deep learning models help in lesion segmentation and classification to differentiate between benign and malignant tumors.

5.4 Pathology and Histopathology Imaging

Digital pathology imaging involves high-resolution microscopic analysis of tissue samples, where deep learning has significantly improved cell and tissue segmentation for cancer diagnosis. In breast cancer histopathology, segmentation models identify malignant regions in hematoxylin and eosin (H&E)-stained tissue slides. Similarly, in prostate and colorectal cancer, CNN-based algorithms assist pathologists by detecting cancerous regions, grading tumor severity, and predicting patient prognosis. Deep learning is also employed in blood cell segmentation for detecting abnormalities in hematological disorders, such as leukemia and anemia.

6. Future and results

Recent advancements in deep learning have significantly improved medical image segmentation by addressing challenges related to data availability, computational efficiency, and model interpretability. Self-supervised and semi-supervised learning techniques have reduced dependency on large annotated datasets by leveraging unlabeled data, leading to improved segmentation accuracy in MRI, CT, and pathology imaging. Similarly, federated learning has enabled privacy-preserving AI models by allowing multiple institutions to collaboratively train models without sharing patient data. This approach has enhanced the generalizability of segmentation models across diverse medical centers, ensuring better performance in real-world clinical settings.

In addition to data-efficient learning, lightweight deep learning models have been developed to support real-time medical applications, enabling segmentation in portable imaging devices, such as ultrasound and mobile MRI scanners. These models maintain high accuracy while reducing computational requirements, making AI-assisted diagnosis more accessible. Furthermore, the focus on explainability and trustworthiness has improved clinical adoption by providing transparent decision-making processes through attention mechanisms and visualization techniques like class activation mapping (CAM). By enhancing model interpretability, deep learning segmentation systems are becoming more reliable, leading to greater acceptance in radiology and pathology workflows, ultimately improving patient care and treatment planning.

7. Conclusion

Deep learning-based segmentation algorithms have transformed medical image analysis by enabling precise, automated, and efficient segmentation of anatomical structures and pathological abnormalities. These models have significantly improved diagnostic accuracy, reduced manual workload for clinicians, and facilitated early disease detection across various imaging modalities, including MRI, CT, ultrasound, and digital pathology. Despite these advancements, challenges such as data dependency, computational costs, and model generalization persist, limiting widespread clinical adoption. However, ongoing research in self-supervised learning, federated learning, and lightweight architectures is addressing these barriers, making deep learning-based segmentation more accessible and scalable for real-world healthcare applications.

To fully harness the potential of deep learning in medical imaging, a hybrid approach that integrates deep learning with traditional image processing and domain-specific knowledge is essential. Combining AI-driven segmentation with expert-driven validation and post-processing techniques ensures higher accuracy and reliability in clinical settings. Additionally, improving model interpretability through explainable AI (XAI) and regulatory compliance will further drive the integration of deep learning-based segmentation into routine medical practice. As these innovations continue to evolve, deep learning holds immense potential to enhance medical diagnostics, personalize treatment strategies, and ultimately improve patient outcomes, shaping the future of AI-driven healthcare.

Reference:

1. Liu, X., Song, L., Liu, S., & Zhang, Y. (2021). A review of deep-learning-based medical image segmentation methods. Sustainability, 13(3), 1224. https://doi.org/10.3390/su13031224 MDPI
2. Wang, R., Lei, T., Cui, R., Zhang, B., Meng, H., & Nandi, A. K. (2020). Medical image segmentation using deep learning: A survey. arXiv preprint arXiv:2009.13120. arXiv
3. Hesamian, M. H., Jia, W., He, X., & Kennedy, P. (2019). Deep learning techniques for medical image segmentation: Achievements and challenges. Journal of Digital Imaging, 32(4), 582–596. https://doi.org/10.1007/s10278-019-00227-x SpringerLink
4. Shen, D., Wu, G., & Suk, H. I. (2017). Deep learning in medical image analysis. Annual Review of Biomedical Engineering, 19, 221–248. https://doi.org/10.1146/annurev-bioeng-071516-044442
5. Litjens, G., Kooi, T., Bejnordi, B. E., Setio, A. A. A., Ciompi, F., Ghafoorian, M., ... & van Ginneken, B. (2017). A survey on deep learning in medical image analysis. Medical Image Analysis, 42, 60–88. https://doi.org/10.1016/j.media.2017.07.005
6. Ronneberger, O., Fischer, P., & Brox, T. (2015). U-Net: Convolutional networks for biomedical image segmentation. In Proceedings of the International Conference on Medical Image Computing and Computer-Assisted Intervention (pp. 234–241). Springer. https://doi.org/10.1007/978-3-319-24574-4_28
7. Çiçek, Ö., Abdulkadir, A., Lienkamp, S. S., Brox, T., & Ronneberger, O. (2016). 3D U-Net: Learning dense volumetric segmentation from sparse annotation. In Proceedings of the International Conference on Medical Image Computing and Computer-Assisted Intervention (pp. 424–432). Springer. https://doi.org/10.1007/978-3-319-46723-8_49
8. Milletari, F., Navab, N., & Ahmadi, S. A. (2016). V-Net: Fully convolutional neural networks for volumetric medical image segmentation. In Proceedings of the 2016 Fourth International Conference on 3D Vision (pp. 565–571). IEEE. https://doi.org/10.1109/3DV.2016.79
9. Isensee, F., Petersen, J., Klein, A., Zimmerer, D., Jaeger, P. F., Kohl, S., ... & Maier-Hein, K. H. (2018). nnU-Net: Self-adapting framework for U-Net-based medical image segmentation. arXiv preprint arXiv:1809.10486.

10. Zhou, Z., Siddiquee, M. M. R., Tajbakhsh, N., & Liang, J. (2018). UNet++: A nested U-Net architecture for medical image segmentation. In Proceedings of the Deep Learning in Medical Image Analysis and Multimodal Learning for Clinical Decision Support (pp. 3–11). Springer. https://doi.org/10.1007/978-3-030-00889-5_1